



Item Description

- Mounting Type-** Surface Mounted
- Housing-** Die-cast Aluminum
- Diffuser-** Opal
- Reflector-** White
- Life Span-** > 50,000 Hrs (Ta = 30°C LM70)
- Input Voltage-** AC 85-265V 50/60Hz
- Option-** Non Dimmable / Dimmable DALI / 0~ 10V/ Triac
- Standards-** EN60598-1 / EN60595-2-1



Objective

XETAR-10-12-20 is strictly designed based on IP65 protection, waterproof, dust proof and corrosion proof performance. Strong aluminum housing+PC cover. It gives high efficiency over 100lm/W.

Perfect heat dissipation with long lifespan 5years warranty. Surface mounted installation. Emergency, Microwave sensor, Dimming optional.

It is suitable for Semi-outdoor ceiling Gas Station Airport , Parking lot, Corridor, Lobby and so on.

CODE	WATTAGE	LUMENS	CRI	KELVINS	DIMENSIONS
XETAR-10	10W	900lm(WW)/960lm(NW)/1000lm(CW)	>80	3000-3150K/4000K-4200K/5800-6100K	323x102x97mm
XETAR-12	12W	1100lm(WW)/1160lm(NW)/1200lm(CW)	>80	3000-3150K/4000K-4200K/5800-6100K	323x102x97mm
XETAR-20	20W	1900lm(WW)/1960lm(NW)/2000lm(CW)	>80	3000-3150K/4000K-4200K/5800-6100K	323x102x97mm



Housing Colours(Optional)



01. White 02. Coffee Color