## bluelunar

CE ROHS Alu. IES IP20

Drivers bluelunor TCI® Helvar

# 

CE RoHS Alu. IES IP20



Mounting Type- Track Housing- Aluminum Diffuser- PC (Optional) Life Span- > 50,000 Hrs (Ta = 30°C LM70) Option- Non Dimmable / Dimmable DALI / 0~ 10V/ Triac Standards- EN60598-1 / EN60595-2-1

#### Objective

Track light with aluminum housing having lens and LED diffuser. Low voltage circuit design and external driver makes it be very safe. Built with magnetic system, the light can be inserted into track easily.

Special asymmetric wall washer lens makes the light be a perfect wall washer light and assure the light output be very even and clean.

#### Item Description


Mounting Type- Track Housing- Aluminum Diffuser- PC (Optional) Life Span- > 50,000 Hrs (Ta = 30°C LM70) Option- Non Dimmable / Dimmable DALI / 0~ 10V/ Triac Standards- EN60598-1 / EN60595-2-1

CODE	WATTAGE	LUMENS	CRI	DIMENS
MAGNET LINE OPAL DROP	18W	1200lm	High	284x72.6x3

. . .

284	9. 22 30.6
[ =•:===== •= == == == = = = = = = = = =	

**Optic Lens** 



www.bluelunar.net

Drivers		Helvar

#### Objective

Track light with aluminum housing having lense and LED diffuser. Low voltage circuit design and external driver makes it be very safe.Built with magnetic system, the light can be inserted into track easily.

Uniue bisymmetric wall washer lens meeting with even strictest vertical illumination reuirements. No shadows, uniform light up to the ceiling level without any tillting of the fixture needed.

**ons** D.6mm

### Optic Lens

