









bluelunor TCI Helvar



Item Description

Mounting Type- Recessed Housing- Die-cast aluminum

Diffuser- Anti-glare

Life Span- > 50,000 Hrs (Ta = 30° C LM70)

Driver- DC700mA | DC700mA

Option- Non Dimmable / Dimmable DALI / 0~ 10V/ Triac

Standards- EN60598-1 / EN60595-2-1

Objective

Recessed mounted circular LED downlights luminaire with die-cast aluminum in white powder coating finish, especially designed heat sink, anti glare diffuser and separate energy efficient electronic.

These are suitable for Living rooms, Corridors, Hotels, Exhibition Halls, Shopping Malls, Brandchain Stores and so on.

| CODE | WATTAGE | LUMENS | CRI | KELVINS | DIMENSIONS |
|---------|---------|------------------|----------|-------------------|------------|
| FLAP-19 | 19W | 1482/1672/1862lm | 90/80/70 | 3000K/4000K/5000K | Ф190x58mm |
| FLAP-24 | 24W | 1872/2112/2352lm | 90/80/70 | 3000K/4000K/5000K | Ф230х66mm |
| FLAP-30 | 30W | 2340/2550/2940lm | 90/80/70 | 3000K/4000K/5000K | Ф230х66тт |















