

Item Description

Mounting Type- Ceiling Recessed

Housing- Aluminum

Diffuser- PMMA

Reflector- White

Life Span- > 50,000 Hrs (Ta = 30°C LM70)

Option- Non Dimmable / Dimmable DALI / 0~ 10V/ Triac

Standards- EN60598-1 / EN60595-2-1




Objective

Using our latest technology to make a combination between decoration & efficiency.

PYROS is round panel with total height inside the ceiling <25mm, aluminum PCB equipped with SMD light source center emitting, aluminum casting body with 2mm thickness of acrylic and 4mm thickness PMMA diffuser..

It can be used in Retails, Residentials and Hotels.

CODE	WATTAGE	LUMENS	CRI	KELVINS	DIMENSIONS	CUTOUT
PYROS-3	3W	180lm	>80	2700-3200K/3800-4200K/5700-6000K	Ø85x24mm	Ø75
PYROS-6	6W	360lm	>80	2700-3200K/3800-4200K/5700-6000K	Ø120x24mm	Ø110
PYROS-9	9W	600lm	>80	2700-3200K/3800-4200K/5700-6000K	Ø145x24mm	Ø135
PYROS-12	12W	850lm	>80	2700-3200K/3800-4200K/5700-6000K	Ø170x24mm	Ø160
PYROS-15	15W	1020lm	>80	2700-3200K/3800-4200K/5700-6000K	Ø200x24mm	Ø190
PYROS-18	18W	1350lm	>80	2700-3200K/3800-4200K/5700-6000K	Ø225x24mm	Ø205
PYROS-24	24W	1650lm	>80	2700-3200K/3800-4200K/5700-6000K	Ø300x24mm	Ø280



01. White 02. Black 03. Silver 04. Grey