



**Item Description**





- Mounting Type-** Recessed
- Housing-** Die-cast Aluminum
- Diffuser-** Opal PC
- Reflector-** Aluminum
- Life Span-** > 50,000 Hrs (Ta = 30°C LM70)
- Option-** Non Dimmable / Dimmable DALI / 0~ 10V/ Triac
- Standards-** EN60598-1 / EN60595-2-1

**Objective**

Recessed mounted circular LED downlight luminance with die-cast aluminum housing in white powder coated finish, specially designed heatsink and separate energy efficient electronic driver.

Suitable for living rooms, corridors, shops, shopping malls & hotels.

CODE	WATTAGE	LUMENS	CRI	KELVINS	DIMENSIONS
FLASH-8	8W	624/680/720lm	90/80/70	3000K/4000K/5000K	Ø100x50mm
FLASH-12	12W	936/1020/1080lm	90/80/70	3000K/4000K/5000K	Ø118x55mm
FLASH-20	20W	1560/1700/1800lm	90/80/70	3000K/4000K/5000K	Ø145x65mm
FLASH-25	25W	1950/2125/2250lm	90/80/70	3000K/4000K/5000K	Ø180x82mm



**Colours**

01 02 03

01. White 02. Black 03. Silk White