



T-SHAPE

UP SQUARE

Heat sink greatly increases the radiation area and improves cooling efficiency.



Item Description

Mounting Type- Recessed
Housing- Die-casting aluminum
Diffuser- Frosted / Clear
Life Span- > 50,000 Hrs (Ta = 30°C LM70)
Option- Non Dimmable / Dimmable DALI / 0~ 10V/ Triac
Standards- EN60598-1 / EN60595-2-1

Objective

Recessed downlight adopts super slim and compact design, perfectly suitable for the narrow ceiling installation. IP65 rating front cover design, suitable for damp environment. Traditional diamond plated surface lens design ensures the high light transmittance and uniform lighting output.

T-shape heat sink greatly increases the radiation area and improves cooling efficiency. The fitting could be rotated from 0 to 30 degree in horizontal direction, which can expand the illumination area.

CODE	WATTAGE	LUMENS	CRI	KELVINS	DIMENSIONS
UP SQUARE-5	5W	465-530lm	80/90	3000K/4000K/5000K/5700K	80*80*30mm cutout Ø68-72mm
UP SQUARE-8	8W	695-815lm	80/90	3000K/4000K/5000K/5700K	80*80*30mm cutout Ø68-72mm
UP SQUARE-10	10W	860-1000lm	80/90	3000K/4000K/5000K/5700K	90*90*39mm cutout Ø75-80mm
UP SQUARE-13	13W	1130-1300lm	80/90	3000K/4000K/5000K/5700K	110*110*50mm cutout Ø90-95mm

