



Matt Surface Specular Faceted

Item Description

- Mounting Type-** Recessed
- Housing-** PC
- Trim-** Die-cast aluminum
- Diffuser-** Opal
- Reflector-** Specular, Faceted
- Life Span-** > 50,000 Hrs (Ta = 30°C LM70)
- Option-** Non Dimmable / Dimmable DALI / 0~ 10V/ Triac
- Standards-** EN60598-1 / EN60595-2-1

Objective

LED downlight model is an integrated downlight provides the perfect combination of efficiency, light comfort and design, without compromising on lighting performance (color rendering and color uniformity). it offers a wide choice for creating the desired ambience.

CODE	WATTAGE	LUMENS	CRI	KELVINS	DIMENSIONS
ULTRA-06	6W	490-610lm	80/90	2700K/3000K/4000K/5000K/5000K	Ø110x70mm
ULTRA-08	8W	680-810lm	80/90	2700K/3000K/4000K/5000K/5000K	Ø110x70mm
ULTRA-13	13W	1250-1460lm	80/90	2700K/3000K/4000K/5000K/5000K	Ø145x82mm
ULTRA-15	15W	1430-1670lm	80/90	2700K/3000K/4000K/5000K/5000K	Ø172x95mm
ULTRA-18	18W	1530-1890lm	80/90	2700K/3000K/4000K/5000K/5000K	Ø172x95mm
ULTRA-25	25W	2330-2930lm	80/90	2700K/3000K/4000K/5000K/5000K	Ø228x98mm

