RoHS Alu. IES IP20





With LED Diffuser

Item Description

Mounting Type- Track Housing- Aluminum Diffuser- PC (Optional)

Life Span- > 50,000 Hrs (Ta = 30°C LM70)

Option- Non Dimmable / Dimmable DALI / 0~ 10V/ Triac

Standards- EN60598-1 / EN60595-2-1

CODE	WATTAGE	LUMENS	CRI	DIMENSIONS
MAGNET SPOT 9 (Lens)	9W	600lm	High	217.5x135x25xmm
MAGNET SPOT 9 (Diffuser)	9W	400lm		217.5x135x25xmm

Objective

Track light with aluminum housing having lens and LED diffuser. Low voltage circuit design and external driver makes it be very safe. Built with magnetic system, the light can be inserted into track easily. Turning connector part makes the light be 355 degree rotatable.

Foldable structure, you can change the beam angle within one minute and adjust it from 0-90 degree. LED diffuser makes the light be very even and soft (Optional, LED lens makes the light be more focused (Optional LED lens), suitable for accent lighting.



With LED Diffuser

Item Description

Mounting Type- Track Housing- Aluminum Diffuser- PC (Optional)

Life Span- $> 50,000 \text{ Hrs (Ta} = 30^{\circ}\text{C LM70)}$

Option- Non Dimmable / Dimmable DALI / 0~ 10V/ Triac


Standards- EN60598-1 / EN60595-2-1

CODE	WATTAGE	LUMENS	CRI	DIMENSIONS
MAGNET SPOT 9x2 (Lens)	9x2W	1200lm	High	266x217.8x25mm
MAGNET SPOT 9x2 (Diffuser)	9x2W	800lm		266x217.8x25mm

Objective

Track light with aluminum housing having lens and LED diffuser. Low voltage circuit design and external driver makes it be very safe. Built with magnetic system, the light can be inserted into track easily. Turning connector part makes the light be 355 degree rotatable.

Foldable structure, you can change the beam angle within one minute and adjust it from 0-90 degree. LED diffuser makes the light be very even and soft (Optional. LED lens makes the light be more focused (Optional LED lens), suitable for accent lighting.



Optic Lens

