bluelunar

CE RoHS Alu. IES IP20





Item Description

Mounting Type- Recessed Housing- Pure Aluminum Heat Sink Diffuser- Frosted / Clear Reflector- Aluminum Life Span- > 50,000 Hrs (Ta = 30°C LM70) Driver- DC200mA | DC250mA Option- Non Dimmable / Dimmable DALI / 0~ 10V/ Triac Standards- EN60598-1 / EN60595-2-1

Objective

JOMON-07-10 LED is made of aluminum alloy through die-casting, shaped by CNC machine and then treated by powder coating. The led driver is installed externally.

COB LED or LED QR-CB51 or QR-CB51 light source is used. The radiation angle is unadjustable, electric appliances are installed externally.

It is best for Hotels, Villas, Clubs, Opera Houses, Museums, Exhibition Centers, Stores & Boutiques.

CODE	WATTAGE	LUMENS	CRI	KELVINS	DIMENSIONS
JOMON-07	7W	494lm	90	2700K/3000K/3500K/4000K/5000K/6500K	Ф100x110mm
JOMON-10	10W	584lm	90	2700K/3000K/3500K/4000K/5000K/6500K	Ф100x110mm



350° Horizontally 0° ~ 30° Tilt 0° 20° Tilt

